



SAT Connection Cable (110 dB)

F connector > F connector

This AINSTEIN SAT connection cable is designed to meet higher requirements of high resolution audio and video transmission (HDTV) for linking devices with F-connectors. The highly conductive oxygen-free copper center conductor takes over the exact signal line. Due to the very high shielding efficiency, the cable ensures interference-free signal trans-

mission and the gold-plated contacts provide maximum signal stability. The processed plugs are made of particularly durable metal and the kink protection ensures optimal strain relief as well as a form-fitting connection. In addition to that the flexible fabric sleeve prevents cable breakage.



 designed by
SCHWAIGER

ARTICLE INFORMATION

Article Nr
EAN

AISA1020 413
4004005011227



Last updated: 14.02.2019



FEATURES (AISA1020 413)

- Cable for connecting a device (F terminal) with a SAT socket
- particularly suitable for HDTV via satellite
- shielded 4 times to effectively reduce electromagnetic interference
- very high shielding efficiency guaranteed
- gold-plated pins offer best-possible conductivity, minimum transmission resistance and high protection against corrosion
- inner conductor made of copper for good signal transmission
- resilient and flexible textile sheath
- plug with kink protection

TECHNICAL DATA

Connections	2x F connector
Form of cable	round
Cable design	1 mm (inner conductor) 3.1 mm (dielectric) 7.5 mm (sheath)
Inner conductor	OFC-Cu (copper with low oxygen content)
Shielding	shielded 4 times
Shielding value	110 dB
Shielding material	aluminium composite film/64-wire aluminium braid/aluminium composite film/96-wire aluminium braid
Plugs	metal gold-plated pin
Cable length	2 m
Colour	space gray
Packaging	carton

