



★★★  
ULTIMATE

30  
dB

47-862  
MHz

0-20 dB

DBG

## Broadband and Post Amplifier (30 dB)

This SCHWAIGER® broadband cable and post amplifier is used for medium-sized distribution systems as a broadband cable network at the house transfer point or as a post amplifier for community antenna systems. In case of overload (distorted image) due to

signals, which are too strong at the interconnection point, the level control can be adjusted as required.



### ARTICLE INFORMATION

Article Nr  
EAN

BN2315 531  
4004005504989



Last updated: 19.11.2018



## FEATURES (BN2315 531)

- usage as booster amplifier in community antenna systems possible
- built-in level control

## TECHNICAL DATA

Quality	ULTIMATE
Connections (input)	1 x F jack (75 ohms)
Connections (output)	1 x F jack (75 ohms)
Output level (max.)	112 dB $\mu$ V (IM 3 EN50083-3)
Frequency range	47 - 862 MHz
Amplification (typical)	30 dB
Level control	20 dB
Noise figure (typical)	5 dB
Power supply	230 V 50 - 60 Hz
Power consumption	5 VA during operation
Colour	black, silver
Dimensions (width)	100 mm
Dimensions (height)	160 mm
Dimensions (depth)	60 mm
Packaging	sealed blister SBL05A

