



devolo Home Control Door/Window Contact

Maximum security, complete versatility

The devolo Home Control Door/Window Contact offers you optimal control over your doors, windows, drawers as well as other sensitive areas of your home. The wireless Door/Window Contact can be set up in a versatile and unobtrusive way. You will immediately be notified of suspicious or unwanted occurrences via text* and e-mail. The wireless sensor offers you numerous possi-

bilities as a door or window contact. In combination with additional devolo Home Control components, it checks the room temperature, controls the lighting and notifies you of unusual movements. * The first 15 text messages are free. In order to receive additional messages, you need to purchase a devolo Home Control message package.



ARTICLE INFORMATION

Article Nr
EAN

DEV9355
4250059693555



Last updated: 25.04.2017



FEATURES (DEV9355)

- Detects open doors, windows or drawers without fail and automatically sends text or e-mail notifications.
- Quick and versatile installation via adhesive film or screws (both in the scope of delivery).
- Continuous brightness and temperature measurement, e.g. as feedback to the light and radiator control
- Intuitive operation via a free Apple iOS and Android app for smartphones, tablets or the computer.
- Unobtrusive design for inconspicuous placement.
- Individually expandable at any time with other devolo Home Control components.
- Future-proof thanks to standardised Z-Wave® wireless technology.
- Highest data security via certified systems in Germany
- No monthly follow-up costs after purchase.
- Comprehensive expert advice via phone, e-mail and live chat.
- content: devolo Home Control Door/Window Contact with battery, mounting accessories, installation manual

TECHNICAL DATA

Integrated protocols	Z-Wave
Frequency range	868,42 MHz
Range	in buildings 25 m outdoor 100 m
Point of use	indoor use
Operating temperature	-10 bis +40 °C
Ambient conditions	10 - 85 % humidity (non-condensing)
Display	LED
Button	1
Battery type	CR123A

Magnet distance (max.)	30 mm
Temperature measurement	-10 - +70 °C
Operating systems	from Windows® 7/Linux® (Ubuntu)/Mac OS® X
Certifications	CE Class B (EU, CH, NO)
Dimensions (width)	28 mm
Dimensions (height)	96 mm
Dimensions (depth)	23 mm
Guarantee	3 years manufacturer's guarantee
Packaging	carton