



devolo Home Control Radiator Thermostat

Intelligent heating, even on the go

The devolo Home Control Radiator Thermostat is an intelligent radiator control, which can be programmed wirelessly or using time control settings. The thermostat gives you the possibility to heat your rooms before you even get home – without having to run the heat all day.

The radiator control automatically switches the desired radiator on or off at your desired time. This helps you save on heating costs and avoid having to enter cold rooms. An illuminated display is used as the visual temperature display and eases monitoring.



ARTICLE INFORMATION

Article Nr DEV9356
EAN 4250059693562



Last updated: 25.04.2017



FEATURES (DEV9356)

- Controls the room temperature via time control depending on your individual daily routine and gives you flexibility for programming each day of the week.
- Holiday mode for maximum energy savings
- Fits all current radiators. Simply replace conventional radiator thermostats.
- Ready to use in no time: can be installed easily, without special tools or expertise.
- Manual temperature control at the thermostat, and intuitive operation via free Apple iOS and Android app for smartphones and tablets or the computer.
- Illuminated display to show temperature
- Connected via Z-Wave® wireless technology to additional devolo Home Control components.
- Individually expandable at any time with other devolo Home Control components.
- Future-proof thanks to standardised Z-Wave® wireless technology.
- Highest data security via certified systems in Germany.
- No monthly follow-up costs after purchase.
- content: devolo Home Control Radiator Thermostat incl. batteries, 2x adapter ring, installation manual

TECHNICAL DATA

Integrated protocols	Z-Wave
Frequency range	868,42 MHz
Range	up to 25 m indoor
Protection class	IP20
Operating temperature	0° - 40 °C
Storage temperature	-20° - 65° °C
Ambient conditions	10 - 90 % humidity (non-condensing)
Display	LCD display
Button	3
Battery type	LR06 (AA)
Synchronisation	adjustable (5 minutes recommended)

Temperature range	4° - 28° °C
Window open function	yes
Water temperature	max. 90 °C
Noise level	< 30 dBA
Operating systems	from Windows® 7/Linux® (Ubuntu)/Mac OS® X
Certifications	CE Class B (EU, CH, NO)
Dimensions (diameter)	51 mm
Dimensions (depth)	91 mm
Guarantee	3 years manufacturer's guarantee
Packaging	carton