



devolo Home Control Room Thermostat

for your personalised comfortable temperature

When combined, the devolo Home Control Room Thermostat and devolo Home Control Radiator Thermostats ensure a consistent temperature throughout your home. The wireless Thermostat measures the temperature at the chosen location. If the values are too low, it reports them to the devolo Home Control Central Unit using standardised Z-Wave® wireless technology. Using this

method, the temperature is adjusted automatically at the Radiator Thermostat until your comfortable temperature has been reached throughout the room. The wireless Room Thermostat also functions as a handy control switch that can be used to centrally control all radiators connected via the devolo Home Control Radiator Thermostat from your sofa or desk.



ARTICLE INFORMATION

Article Nr
EAN

DEV9361
4250059693616



Last updated: 25.04.2017



FEATURES (DEV9361)

- Easy and central unit control of the room temperature (when combined with the devolo Home Control Radiator Thermostats).
- Comfortable temperatures exactly where you spend time, not just at the radiator.
- Manual temperature control at the touch of a button, right at the Room Thermostat, as well as intuitive operation of the free Apple iOS and Android app for smartphones, tablets and computers.
- Illuminated display to show temperature.
- Quick and versatile installation via adhesive film or screws (both in the scope of delivery).
- Ready to use in no time: can be installed easily and safely, without special tools or expertise.
- Individually expandable at any time with other devolo Home Control components.
- Future-proof thanks to standardised Z-Wave® wireless technology.
- Highest data security via certified systems in Germany.
- content: devolo Home Control Room Thermostat, 2 batteries, mounting accessories, installation manual

TECHNICAL DATA

Integrated protocols	Z-Wave
Frequency range	868,42 MHz
Range	up to 25 m indoor up to 100 m outdoor
Protection class	IP21 (indoors)
Operating temperature	0° - 40 °C
Ambient conditions	10 - 95 % humidity (non-condensing)
Display	LCD display
Button	3, of which 1 includes LED

Battery type	LR06 (AA)
Operating systems	from Windows® 7/Linux® (Ubuntu)/Mac OS® X
Certifications	CE Class B (EU, CH, NO)
Dimensions (width)	75 mm
Dimensions (height)	75 mm
Dimensions (depth)	24 mm
Guarantee	3 years manufacturer's guarantee
Packaging	carton

Last updated: 25.04.2017