



★★★  
ULTIMATE



## DiSEqC 1.0 Switch (2 > 1) with weather-resistant housing

This SCHWAIGER® DiSEqC switch is used to distribute 2 single LNBs to 1 subscriber (receiver). Satellite positions can be selected via DiSEqC commands or via Toneburst signals. The DiSEqC commands desired can

be set via a selector switch. This device can also be used to interconnect multi switches.



### ARTICLE INFORMATION

Article Nr  
EAN

KFR7025 531  
4004005012828



Last updated: 23.03.2016



## FEATURES (KFR7025 531)

- DiSEqC switch distributes 2 universal single LNBs to 1 subscriber
- SAT multi-switches can be connected via outputs
- selection of the satellite position via DiSEqC or Toneburst signal
- selector switch for DiSEqC commands "Position SA/SB" or "Option A/B"
- weather-resistant housing for outdoor installation
- digital ready
- Direct Current pass (DC)

## TECHNICAL DATA

quality	*** Ultimate
Point of use	outdoor use
Connections (input)	2x F jack
Connections (output)	1x F jack
Frequency range	5 - 2150 MHz
Control function	DiSEqC 1.0
Transmission loss	< 4 dB

Power supply	13/18 V
Colour	silver
Dimensions (width)	48 mm
Dimensions (height)	92 mm
Dimensions (depth)	29 mm
packaging	sealed blister SBL04

Last updated: 23.03.2016