



★★★★
ULTIMATE



SAT Coaxial Cable (115 dB)

This SCHWAIGER® coaxial cable is suitable for very high requirements with satellite and cable TV systems. The 115 dB shielding provides best possible protection against electromagnetic signal interference and radio interference of any kind. In addition, the cable

structure makes for very low signal attenuation. The cable can be shortened as desired and can be equipped with the F connectors included. SCHWAIGER® offers a suitable stripping tool.



ARTICLE INFORMATION

Article Nr
EAN

KOX11515 532
4004005019803



4 004005 019803

Last updated: 23.03.2016



FEATURES (KOX11515 532)

- shielded 3 times for additional protection against electromagnetic signal interference
- high shielding efficiency guaranteed
- moisture-resistant with high long-term stability
- high density and very good shielding efficiency
- set consisting of: + coaxial cable (115 dB), shielded 3 times + 2x Ø 7 mm F connector (Schwaiger FST 70xx)

TECHNICAL DATA

quality	*** Ultimate
Norm/Classification	class A
Impedance	75 Ohm
Cable design	1.02 mm (inner conductor) 4.4 mm (dielectric) 7 mm (sheath)
Shielding value	115 dB
Shielding	shielded 3 times
Shielding material	aluminium composite film (double)/84-wire aluminium braid/aluminium composite film (double)

Attenuation on 100 m	5 dB up to 50 MHz
	6 dB up to 100 MHz
	14 dB up to 470 MHz
	20 dB up to 860 MHz
	21 dB up to 950 MHz
	29 dB up to 1750 MHz
	33 dB up to 2150 MHz

Inner conductor	CU
Cable length	15 m
Material of product	plastic
Colour	white
packaging	sealed blister SBL11

Last updated: 23.03.2016