



★★★
ULTIMATE



SAT Coaxial Cable (115 dB)

This SCHWAIGER® coaxial cable is suitable for very high requirements with satellite and cable TV systems. The 115 dB shielding provides best possible protection against electromagnetic signal interference and radio interference of any kind. In addition, the cable

structure makes for very low signal attenuation. The cable can be shortened as desired and can be equipped with the F connectors included. SCHWAIGER® offers a suitable stripping tool.



ARTICLE INFORMATION

Article Nr
EAN

KOX11525 532
4004005019810



Last updated: 23.03.2016



FEATURES (KOX11525 532)

- shielded 3 times for additional protection against electro-magnetic signal interference
- high shielding efficiency guaranteed
- moisture-resistant with high long-term stability
- high density and very good shielding efficiency
- set consisting of: + coaxial cable (115 dB), shielded 3 times + 2x Ø 7 mm F connector (Schwaiger FST 70xx)

TECHNICAL DATA

quality	*** Ultimate
Norm/Classification	class A
Impedance	75 Ohm
Cable design	1.02 mm (inner conductor) 4.4 mm (dielectric) 7 mm (sheath)
Shielding value	115 dB
Shielding	shielded 3 times
Shielding material	aluminium composite film (double)/84-wire aluminium braid/aluminium composite film (double)
Attenuation on 100 m	5 dB up to 50 MHz 6 dB up to 100 MHz 14 dB up to 470 MHz 20 dB up to 860 MHz 21 dB up to 950 MHz 29 dB up to 1750 MHz 33 dB up to 2150 MHz

Inner conductor	CU
Cable length	25 m
Material of product	plastic
Colour	white
packaging	sealed blister SBL11

Last updated: 23.03.2016