



★★★
ULTIMATE



SAT Installation Kit (120 dB)

This SCHWAIGER[®] set is suitable for higher requirements with satellite and cable TV systems. The 120 dB shielding provides best possible protection against electromagnetic signal interference and radio interference of any kind. In addition, the cable structure

makes for very low signal attenuation. The cable can be shortened as desired and can be equipped with the F connectors included. SCHWAIGER[®] offers a suitable stripping tool.



ARTICLE INFORMATION

Article Nr
EAN

KOX120 100
4004005120820



Last updated: 23.03.2016



FEATURES (KOX120 100)

- shielded 4 times to effectively reduce electromagnetic interference
- high shielding efficiency guaranteed
- moisture-resistant with high long-term stability
- high density and very good shielding efficiency
- coaxial cable with meter coding on plastic spool
- set consists of:
 - 1x coaxial cable, 120 dB
 - 10x F connector, Ø 7.5 mm

TECHNICAL DATA

quality	*** Ultimate
Norm/Classification	class A
Impedance	75 Ohm
Cable design	1.02 mm (inner conductor) 4.5 mm (dielectric) 7.5 mm (sheath)
Shielding value	120 dB
Shielding	shielded 4 times
Shielding material	aluminium composite film/64-wire aluminium braid/aluminium composite film/82-wire aluminium braid
Attenuation on 100 m	4,7 dB up to 50 MHz 6,3 dB up to 100 MHz 8,7 dB up to 200 MHz 13,4 dB up to 470 MHz 18,0 dB up to 800 MHz 18,6 dB up to 860 MHz 19,4 dB up to 950 MHz 28,4 dB up to 1750 MHz 31,9 dB up to 2150 MHz 34,1 dB up to 2400 MHz

Inner conductor	CU
Cable length	100 m
Material of product	plastic
Colour	white
packaging	spool

Last updated: 23.03.2016