



☆☆☆  
PROFESSIONAL

20m  
↔

75  
dB

12,8  
mm

## SAT Quattro Coaxial Cable (75 dB)

This SCHWAIGER® coaxial cable is used with satellite and cable TV systems. It is perfect for narrow cable shafts. Each of the four colour-coded cable strands is doubly shielded, which makes for less signal interference. The cable can be shortened to any length desired and

be equipped with compatible F connectors. A suitable stripping tool is available from SCHWAIGER®.



### ARTICLE INFORMATION

Article Nr  
EAN

KOX44/20 012  
4004005440027



4 004005 440027

Last updated: 23.03.2016



## FEATURES (KOX44/20 012)

- 4 integrated cable strands, individually shielded and labelled with colours
- suitable for subsequent installation and direct connection to LNBS
- shielded twice for low susceptibility to electromagnetic interference
- high shielding efficiency guaranteed
- moisture-resistant with high long-term stability
- high density and very good shielding efficiency

## TECHNICAL DATA

quality	** Professional
Form of cable	round
Impedance	75 Ohm
Cable design	0.5 mm (inner conductor) 3.8 mm (dielectric) 12.8 mm (outer coat)
Shielding value	up to 1000 MHz up to 2400 MHz
Shielding	shielded twice
Shielding material	64-wire aluminium braid/aluminium composite film
Attenuation on 100 m	1,7 dB with 47 MHz 2,2 dB with 100 MHz 4,6 dB with 470 MHz 7 dB with 860 MHz 7,5 dB with 950 MHz 10 dB with 1750 MHz 11,3 dB with 2150 MHz

Inner conductor	CU
Cable length	20 m
Material of product	plastic
Colour	white
packaging	carton

Last updated: 23.03.2016