



☆☆☆  
STANDARD

10 m  
↔

75  
dB

∅  
6,5  
mm

## SAT Coaxial Cable (75 dB)

This SCHWAIGER® coaxial cable is suitable for satellite and cable TV systems. It is shielded twice and, thus, better protected against any kind of signal interference. The cable can be shortened to any length desired and be equipped with compatible F connectors. A

suitable stripping tool is available from SCHWAIGER®.



### ARTICLE INFORMATION

Article Nr  
EAN

KOX510 052  
4004005203318



4 004005 203318

Last updated: 23.03.2016



## FEATURES (KOX510 052)

- shielded twice for low susceptibility to electromagnetic interference
- extremely flexible and easy to lay
- cable is equipped with meter coding
- suitable F connectors: Ø 6.5 mm (FST 65xx)

## TECHNICAL DATA

quality	* Standard
Form of cable	round
Impedance	75 Ohm
Cable design	0.5 mm (inner conductor) 4.4 mm (dielectric) 6.5 mm (sheath)
Shielding value	75 dB
Shielding	shielded twice
Shielding material	32-wire aluminium braid/aluminium composite film
Attenuation on 100 m	5 dB with 50 MHz 20 dB with 470 MHz 28 dB with 860 MHz 30 dB with 950 MHz 40 dB with 1750 MHz 44 dB with 2150 MHz

Inner conductor	CCS
Cable length	10 m
Material of product	plastic
Colour	white
packaging	shrink foil

Last updated: 23.03.2016