



☆☆☆
STANDARD

15 m
↔

75
dB

∅
6,5
mm

2x
shielded

SAT Coaxial Cable (75 dB)

This SCHWAIGER® coaxial cable is suitable for satellite and cable TV systems. It is shielded twice and, thus, better protected against any kind of signal interference. The cable can be shortened to any length desired and be equipped with compatible F connectors. A

suitable stripping tool is available from SCHWAIGER®.



ARTICLE INFORMATION

Article Nr
EAN

KOX515 052
4004005203325



4 004005 203325

Last updated: 20.01.2017



(KOX515 052)

- shielded twice for low susceptibility to electromagnetic interference
- extremely flexible and easy to lay
- cable is equipped with meter coding
- suitable F connectors: Ø 6.5 mm (FST 65xx)

TECHNICAL DATA

quality	* Standard
Colour	white
Form of cable	round
Impedance	75 Ohm
Cable design	0.5 mm (inner conductor) 4.4 mm (dielectric) 6.5 mm (sheath)
Shielding	shielded twice
Shielding value	75 dB
Shielding material	32-wire aluminium braid/aluminium composite film

Attenuation on 100 m	5 dB with 50 MHz
	20 dB with 470 MHz
	28 dB with 860 MHz
	30 dB with 950 MHz
	40 dB with 1750 MHz
	44 dB with 2150 MHz

Inner conductor	CCS
Cable length	15 m
Material of product	plastic
packaging	shrink foil

Last updated: 20.01.2017