



☆☆☆
PROFESSIONAL



SAT Coaxial Cable (90 dB)

This SCHWAIGER® coaxial cable is suitable for high requirements with satellite and cable TV systems. Due to its higher screening efficiency of 90 dB, it offers additional protection against electromagnetic interference. The cable can be shortened as

desired and then be equipped with compatible F connectors. SCHWAIGER® offers a suitable stripping tool.



ARTICLE INFORMATION

Article Nr
EAN

KOX720 052
4004005720044



Last updated: 23.03.2016



FEATURES (KOX720 052)

- shielded 3 times for additional protection against electromagnetic signal interference
- high shielding efficiency guaranteed
- moisture-resistant with high long-term stability
- high density and very good shielding efficiency

TECHNICAL DATA

quality	** Professional	Attenuation on 100 m	4,3 dB up to 50 MHz
Norm/Classification	class A		6,1 dB up to 100 MHz
Impedance	75 Ohm		13 dB up to 470 MHz
Cable design	1.02 mm (inner conductor)		18,5 dB up to 860 MHz
	4.5 mm (dielectric)		21 dB up to 950 MHz
	7 mm (sheath)		27 dB up to 1750 MHz
Shielding value	up to 1000 MHz > 95 dB		31 dB up to 2150 MHz
	up to 2150 MHz > 90 dB	Inner conductor	CCS
Shielding	shielded 3 times	Cable length	20 m
Shielding material	aluminium composite film/80-wire	Material of product	plastic
	aluminium braid/aluminium composite film	Colour	white
		packaging	shrink foil

Last updated: 23.03.2016