



☆☆☆
PROFESSIONAL



SAT Coaxial Cable (90 dB)

This SCHWAIGER® coaxial cable is suitable for high requirements with satellite and cable TV systems. Due to its higher screening efficiency of 90 dB, it offers additional protection against electromagnetic interference. The cable can be shortened as

desired and then be equipped with compatible F connectors. SCHWAIGER® offers a suitable stripping tool.



ARTICLE INFORMATION

Article Nr
EAN

KOX730 052
4004005153101



Last updated: 23.03.2016



FEATURES (KOX730 052)

- shielded 3 times for additional protection against electromagnetic signal interference
- high shielding efficiency guaranteed
- moisture-resistant with high long-term stability
- high density and very good shielding efficiency

TECHNICAL DATA

quality	** Professional
Norm/Classification	class A
Impedance	75 Ohm
Cable design	1.02 mm (inner conductor) 4.5 mm (dielectric) 7 mm (sheath)
Shielding value	up to 1000 MHz > 95 dB up to 2150 MHz > 90 dB
Shielding	shielded 3 times
Shielding material	aluminium composite film/80-wire aluminium braid/aluminium composite film

Attenuation on 100 m	4,3 dB up to 50 MHz 6,1 dB up to 100 MHz 13 dB up to 470 MHz 18,5 dB up to 860 MHz 21 dB up to 950 MHz 27 dB up to 1750 MHz 31 dB up to 2150 MHz
----------------------	--

Inner conductor	CCS
Cable length	30 m
Material of product	plastic
Colour	white
packaging	shrink foil

Last updated: 23.03.2016