



☆☆☆
STANDARD

100 m
↔

75
dB

∅
6,5
mm

SAT Coaxial Cable (75 dB)

This SCHWAIGER® coaxial cable is suitable for satellite and cable TV systems. It is double-shielded and, thus, less susceptible to electromagnetic interference from the outside. The cable can be shortened as desired and then

be equipped with compatible F connectors. SCHWAIGER® offers a suitable stripping tool.



ARTICLE INFORMATION

Article Nr
EAN

KOX80/100 012
4004005481013



Last updated: 23.03.2016



FEATURES (KOX80/100 012)

- shielded twice for low susceptibility to electromagnetic interference
- extremely flexible and easy to lay
- cable is equipped with meter coding
- suitable F connectors: Ø 6.5 mm (FST 65xx)

TECHNICAL DATA

quality	* Standard
Impedance	75 Ohm
Cable design	0.5 mm (inner conductor) 4.4 mm (dielectric) 6.5 mm (sheath)
Shielding value	up to 470 MHz > 75 dB up to 862 MHz > 75 dB up to 2150 MHz > 65 dB
Shielding	shielded twice
Shielding material	32-wire aluminium braid/aluminium composite film

Attenuation on 100 m	5 dB with 50 MHz
	20 dB with 470 MHz
	28 dB with 860 MHz
	30 dB with 950 MHz
	40 dB with 1750 MHz
	44 dB with 2150 MHz

Inner conductor	CCS
Cable length	100 m
Material of product	plastic
Colour	white
packaging	shrink foil

Last updated: 23.03.2016