



☆☆☆
STANDARD

10 m
↔

75
dB

∅
6,5
mm

SAT Coaxial Cable (75 dB)

This SCHWAIGER® coaxial cable is suitable for satellite and cable TV systems. It is double-shielded and, thus, less susceptible to electromagnetic interference from the outside. The cable can be shortened as desired and then

be equipped with compatible F connectors. SCHWAIGER® offers a suitable stripping tool.



ARTICLE INFORMATION

Article Nr
EAN

KOX80/10 042
4004005480108



4 004005 480108

Last updated: 24.03.2016



FEATURES (KOX80/10 042)

- shielded twice for low susceptibility to electromagnetic interference
- extremely flexible and easy to lay
- cable is equipped with meter coding
- suitable F connectors: Ø 6.5 mm (FST 65xx)

TECHNICAL DATA

Impedance	75 Ohm
Cable design	0.5 mm (inner conductor) 4.4 mm (dielectric) 6.5 mm (sheath)
Shielding value	up to 470 MHz > 75 dB up to 862 MHz > 75 dB up to 2150 MHz > 65 dB
Shielding	shielded twice
Shielding material	32-wire aluminium braid/aluminium composite film
Attenuation on 100 m	5 dB with 50 MHz 20 dB with 470 MHz 28 dB with 860 MHz 30 dB with 950 MHz 40 dB with 1750 MHz 44 dB with 2150 MHz

Inner conductor	CCS
Cable length	10 m
Material of product	plastic
Colour	white
packaging	shrink foil

Last updated: 24.03.2016