



☆☆☆
STANDARD



SAT Coaxial Cable (75 dB)

This SCHWAIGER[®] coaxial cable is suitable for satellite and cable TV systems. It is double-shielded and, thus, less susceptible to electromagnetic interference from the outside. The cable can be shortened as desired and then

be equipped with compatible F connectors. SCHWAIGER[®] offers a suitable stripping tool.



ARTICLE INFORMATION

Article Nr KOX80/15 042
EAN 4004005480153



Last updated: 24.01.2017



(KOX80/15 042)

- shielded twice for low susceptibility to electromagnetic interference
- extremely flexible and easy to lay
- cable is equipped with meter coding
- suitable F connectors: Ø 6.5 mm (FST 65xx)

TECHNICAL DATA

Colour	white
Impedance	75 Ohm
Cable design	0.5 mm (inner conductor) 4.4 mm (dielectric) 6.5 mm (sheath)
Shielding	shielded twice
Shielding value	75 dB
Shielding material	32-wire aluminium braid/aluminium composite film
Attenuation on 100 m	5 dB with 50 MHz 20 dB with 470 MHz 28 dB with 860 MHz 30 dB with 950 MHz 40 dB with 1750 MHz 44 dB with 2150 MHz

Inner conductor	CCS
Cable length	15 m
Material of product	plastic
Packaging	shrink foil

Last updated: 24.01.2017