



☆☆☆
STANDARD



Digital Single LNB

This SCHWAIGER® Single LNB, which is also suitable for multifeed systems, is used to establish a digital-enabled satellite system for 1 subscriber (receiver). The rubber grommet

included protects the F connector against weather exposure.



ARTICLE INFORMATION

Article Nr
EAN

LNB1
4004005001907



Last updated: 21.02.2017



**LOW
NOISE**
Rauscharm

(LNB1)

- reception system for setting up a satellite system for 1 subscriber
- suitable for multifeed systems
- F connectors protected by weather-resistant rubber grommet
- weather protection due to weather-resistant plastic cover

TECHNICAL DATA

Quality	* Standard
Reception system	SINGLE (1 subscriber)
Connections	1x F jack
Input frequency	10,70 - 11,70 GHz (low) 11,70 - 12,75 GHz (high)
Output frequency	950 - 2,150 MHz
Oscillation frequency	9,75 GHz (low) 10.6 GHz (high)
Control function	0 kHz (low) 22 kHz (high)
Polarisation	isolation: > 25 dB
Power supply	vertical: 11,5 - 14,0 V supply voltage horizontal: 16,0 - 19,0 V supply voltage
Feed diameter	40 mm
Material of product	plastic weather-resistant
Colour	light gray
Dimensions (width)	39 mm
Dimensions (height)	100 mm
Dimensions (depth)	54 mm
Product code	21.02.2017
Packaging	carton

