



☆☆☆  
STANDARD

**HD TV** tauglich  
suitable

**HDMI**  
HIGH DEFINITION MULTIMEDIA INTERFACE



## Camping Satellite System

portable

This SCHWAIGER® satellite system is suitable for HDTV and has been put together for portable use in particular. It allows for reception of all free and encrypted TV and radio stations via satellite. It is a complete set for one subscriber. All components are

perfectly matched. This small mobile satellite system comes in a transport case and includes all the accessories necessary for mounting.

### ARTICLE INFORMATION

Article Nr  
EAN

SAT3400HD  
4004005026054



## FEATURES (SAT3400HD)

- SET consists of:
  - » 1x Steel Offset Antenna (35 cm)
  - » 1x Digital Single LNB
  - » 1x FULL HD Satellite Receiver
  - » 1x SAT Connection Cable (75 dB)
  - » 1x High Speed HDMI® Cable with Ethernet
- reception system for setting up a satellite system for 1 subscriber
- independent reception of all available channels for the subscriber of this reception system
- all necessary mounting accessories included
- Solid carrying case for easy storage and transport of all components
- content: 1x Aluminium Offset Antenna, 1x Digital Single LNB, 1x Receiver, 1x SAT Connection Cable, 1x Transport Case

## TECHNICAL DATA

Colour light grey

## STEEL OFFSET ANTENNA (35 CM)

### TECHNICAL DATA

Packaging plastic case

## DIGITAL SINGLE LNB

- reception system for setting up a satellite system for 1 subscriber
- suitable for multifeed systems
- F connectors protected by weather-resistant rubber grommet
- weather protection due to weather-resistant plastic cover
- content: 1x Digital Single LNB

### TECHNICAL DATA

Quality	STANDARD	Polarisation	isolation: > 25 dB
Reception system	SINGLE (1 subscriber)	Power supply	vertical: 11,5 - 14,0 V horizontal: 16,0 - 19,0 V
Connections	1x F jack	Feed diameter	40 mm
Input frequency	10,70 - 11,70 GHz (low) 11,70 - 12,75 GHz (high)	Material of product	plastic weather-resistant
Output frequency	950 - 2,150 MHz	Colour	light grey
Oscillation frequency	9,75 GHz (low) 10.6 GHz (high)	Dimensions (width)	39 mm
Control function	0 kHz (low) 22 kHz (high)	Dimensions (height)	100 mm
		Dimensions (depth)	54 mm
		Packaging	carton

## FULL HD SATELLITE RECEIVER

- HDTV & SDTV SAT receiver
- pre-programmed channel list (ASTRA 19.2°)
- USB interface for service purposes
- USB interface for connecting external memory devices
- 7-day Electronic Programme Guide (EPG) (dependent on channel)
- event timer can be programmed via EPG
- multifunctional timer
- multilingual screen menu
- All Channels list and Favourite Channels list
- teletext with subtitle function
- media player for music, pictures and movies integrated

- indication of signal strength and signal quality for best-possible antenna alignment
- environmentally friendly due to low consumption in sleep mode

- supports Unicable DCSS-LNB up to 32 participants
- content: 1x receiver, 1x remote control, 2x battery (1.5 V LR03 (AAA)), user manual

## TECHNICAL DATA

Type of receiver	SAT (DVB-S2)
Display	indicator light(s)
Programme memory	3000
LNB IN (F-type)	1x (back)
USB 2.0 port	1x (back) 1x (left side of the device)
HDMI® Connection	1x (back)
Resolution	576i/576p/720p/1080i/Full HD 1080p
Audio/video output	1x (back) digital
Infrared connection	1x (back)
Control function	DiSEqC 1.0/1.1/1.2/USALS
Software update	via USB

Languages (Menu)	german/english/french/italian/ persian/turkish
Favourite channels list	8
Remote control	yes
Input frequency	950 - 2150 MHz
Power consumption	in sleep mode < 0,5 W during operation < 5 W
Power supply	176 - 264 V AC , 50 Hz
Colour	black
Dimensions (width)	220 mm
Dimensions (height)	45 mm
Dimensions (depth)	135 mm
Packaging	carton

## SAT CONNECTION CABLE (75 DB)

- shielded twice for low susceptibility to electromagnetic interference
- solid nickel-plated internal PIN

- solid F connector, moulded on both sides
- connector with knurled nut
- content: 1x SAT connection cable

## TECHNICAL DATA

Quality	BASIC
Connections	2x F connector
Impedance	75 Ohm
Plugs	plastic fully shielded
Cable design	0.5 mm (inner conductor) 2.8 mm (dielectric) 5 mm (sheath)

Shielding	shielded twice
Shielding value	> 75 dB
Shielding material	aluminium composite film/64-wire braid
Cable length	10 m
Colour	white
Packaging	paper strip

## HIGH SPEED HDMI® CABLE WITH ETHERNET

- High Speed HDMI® Cable with Ethernet for perfect, high-resolution Ultra HD transmission
- integrated ethernet channel allows for transmitting network data (up to 100 Mbit/s)

- solid plastic plug with moulded strain relief
- 3D transmission with a resolution of up to 1080p
- content: 1x HDMI connection cable

## TECHNICAL DATA

Connections	2x HDMI <sup>®</sup> Connector
Colour	black
Form of cable	round
Data transfer	18 Gbit/s
Resolution	4K (4096 x 2160)
3D transmission	yes

Plugs	plastic moulded
Cable length	1.3 m
note	The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries.
Packaging	paper strip with euro hole