SCHWAIGER®

HD TV tauglich suitable

HDMI HIGH-DEFINITION MULTIMEDIA INTERFACE

MOBIL | ALU | Ø 35 cm | SINGLE LNB | max. 1 | 12 V tauglich | HDMI

Camping Satellite System

für den mobilien Einsatz

This SCHWAIGER® satellite system is suitable for HDTV and has been put together for portable use in particular. It allows for reception of all free and encrypted TV and radio stations via satellite. It is a complete set for one subscriber. All components are perfectly matched. This small mobile satellite system comes in a transport case and includes all the accessories necessary for mounting.

ARTICLE INFORMATION

Article Nr	SAT3612HD
EAN	4004005022001

4 004005 022001

Last updated: 21.11.2017

Errors, variations and changes concerning technical data and illustrations are subject to change. Our General Terms and Conditions for the Supply of Goods and Services apply.

FEATURES (SAT3612HD)

- reception system for setting up a satellite system for 1 subscriber
- independent reception of all available channels for the subscriber of this reception system
- set consists of: 1x aluminium offset antenna (Ø 35 cm), light gray, with suction foot and mounting accessories 1x digital single LNB for one subscriber, light gray 1x Full HDTV satellite receiver, black, 12 V, external 4-digit LED display, 6000 channel memory slots, Timeshift function (with ext. USB memory device), Multimedia Player (photos, music), EPG, preprogrammed channel list and much more 1x 10 m SAT coaxial cable, white; 2x F connector (loose) 1x 1.5 m High-Speed-HDMI cable, suitable for Full HD (1080p), black 1x 12 V DC car connection cable 1x sturdy transport case for easy storage and transport of all components

TECHNICAL DATA

Mounting type	mounting on walls or masts
Colour	light gray
Point of use	outdoor use
Connections (LNB)	1x F jack
Frequency range	950 - 2150 MHz
Control function	DiSEqC 1.0/DiSEqC 1.2/Unicable (SCR)/USALS
Power supply	100 - 240 V AC , 50/60 Hz 12 V DC , 1500 mA
Power consumption	in sleep mode < 1 W during operation < 5,5 W
Reflector dimensions (width)	320 mm
Reflector dimensions (height)	420 mm
Feed diameter	40 mm
Elevation range	20 - 62 °
note	The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries.
Packaging	carton

Last updated: 21.11.2017

Errors, variations and changes concerning technical data and illustrations are subject to change. Our General Terms and Conditions for the Supply of Goods and Services apply.