



HD TV *tauglich
suitable*



Camping SAT set

portable

This HDTV-compatible SCHWAIGER® satellite system is specially designed for mobile use. With this package, all free-to-air television and radio programmes can be received via satellite. It is a complete package for direct connection to a TV with integrated satellite

tuner. All components are optimally matched to each other. The small mobile satellite system is supplied in a transport case and contains all the installation accessories.

ARTICLE INFORMATION

Article Nr
EAN

SATSET351
4004005034134



FEATURES (SATSET351)

- SET consists of:
 - » 1x Steel Offset Antenna (35 cm)
 - » 1x Digital Single LNB
 - » 1x SAT Connection Cable (10 m, 75 dB)
- reception system for setting up a satellite system for 1 subscriber
- independent reception of all available channels for the subscriber of this reception system
- all necessary mounting accessories included
- Solid carrying case for easy storage and transport of all components

TECHNICAL DATA

Colour light grey

STEEL OFFSET ANTENNA (35 CM)

TECHNICAL DATA

Colour light grey Packaging plastic case

DIGITAL SINGLE LNB

- reception system for setting up a satellite system for 1 subscriber
- suitable for multifeed systems
- F connectors protected by weather-resistant rubber grommet
- weather protection due to weather-resistant plastic cover
- content: 1x Digital Single LNB

TECHNICAL DATA

Quality	STANDARD	Polarisation	isolation: > 25 dB
Reception system	SINGLE (1 subscriber)	Power supply	vertical: 11,5 - 14,0 V horizontal: 16,0 - 19,0 V
Connections	1x F jack	Feed diameter	40 mm
Input frequency	10,70 - 11,70 GHz (low) 11,70 - 12,75 GHz (high)	Material of product	plastic weather-resistant
Output frequency	950 - 2,150 MHz	Colour	light grey
Oscillation frequency	9,75 GHz (low) 10.6 GHz (high)	Dimensions (width)	39 mm
Control function	0 kHz (low) 22 kHz (high)	Dimensions (height)	100 mm
		Dimensions (depth)	54 mm
		Packaging	carton

SAT CONNECTION CABLE (10 M, 75 DB)

- shielded twice for low susceptibility to electromagnetic interference
- solid nickel-plated internal PIN
- solid F connector, moulded on both sides
- connector with knurled nut
- content: 1x SAT connection cable

TECHNICAL DATA

Quality	BASIC
Connections	2x F connector
Cable length	10 m
Impedance	75 Ohm
Plugs	plastic fully shielded
Cable design	0.5 mm (inner conductor)
	2.8 mm (dielectric)
	5 mm (sheath)

Shielding	shielded twice
Shielding value	> 75 dB
Shielding material	aluminium composite film/64-wire braid
Colour	white
Packaging	paper strip