



DiSEqC 2.0 Switch (4 > 1)

DiSEqC with weather-resistant housing

This SCHWAIGER® DiSEqC switch is used to distribute 4 single LNBs to 1 subscriber (receiver). Satellite positions can be selected via DiSEqC commands. Remote power supply

of the LNBs is made via the connected receiver.



ARTICLE INFORMATION

Article Nr
EAN

SEW4041 211
4004005404128



Last updated: 26.02.2017



(SEW4041 211)

- DiSEqC switch distributes 4 universal single LNBs to 1 subscriber
- selection of satellite position via DiSEqC signal
- remote power supply of LNBs via connected receiver
- weather-resistant housing for outdoor installation
- easy installation
- Direct Current pass (DC)

TECHNICAL DATA

Colour	black, silver
Point of use	outdoor use
Classification	EN50083-2
Connections (input)	4x F jack (75 ohms)
Connections (output)	1x F jack (75 ohms)
Frequency range	950 - 2300 MHz
Control function	DiSEqC 2.0
Transmission loss	4 dB

Power consumption	20 mA
Material of product	Steel splashproof
Power supply	from the receiver: 13/18 V
Dimensions (width)	120 mm
Dimensions (height)	135 mm
Dimensions (depth)	50 mm
Packaging	carton

Last updated: 26.02.2017