



PROFESSIONAL **HD TV** *tauglich
suitable*



Digital Twin LNB

with weather-resistant cover

With this SCHWAIGER® Twin LNB, which is suitable for multifeed systems, you can establish a digital-enabled satellite system for up to two subscribers. The F connections are

protected by an extendible weather-resistant cover.



ARTICLE INFORMATION

Article Nr
EAN

SPS6514H 531
4004005528312



4 004005 528312

Last updated: 27.03.2017



**LOW
NOISE**
Rauscharm

(SPS6514H 531)

- reception system for setting up satellite systems for 2 subscribers
- suitable for multifeed systems
- F connectors are protected by extendible weather-resistant cover
- weather protection due to weather-resistant plastic cover
- fully encapsulated housing

TECHNICAL DATA

Quality	** Professional
Reception system	TWIN (2 subscribers)
Connections	2x F jack
Input frequency	10,7 - 11,7 GHz (low) 11,7 - 12,75 GHz (high)
Output frequency	950 - 2,150 MHz
Isolation	> 25 dB
Oscillation frequency	9,75 GHz (low) 10,6 GHz (high)
Amplification (typical)	> 55 dB
Control function	0 kHz (low) 22 kHz (high)

Polarisation	isolation: > 25 dB
Power supply	vertical: 10,5 - 14 V horizontal: 6 - 19 V
Power consumption	typ. < 220 mA
Feed diameter	40 mm
Material of product	plastic weather-resistant
Colour	light gray
Dimensions (width)	112 mm
Dimensions (height)	100 mm
Dimensions (depth)	25 mm
Packaging	clamshell SF

Last updated: 27.03.2017