



☆☆☆  
PROFESSIONAL



## Digital Quattro LNB

with weather-resistant cover

This SCHWAIGER® Quattro LNB, which is suitable for multifeed systems, is used to establish a digital-enabled satellite system for more than 4 subscribers (when used together with a multi switch). The F connections of the

LNB are protected by an extendible weather-resistant cover.



### ARTICLE INFORMATION

Article Nr  
EAN

SPS6518H 531  
4004005528329



Last updated: 27.03.2017



**LOW  
NOISE**  
Rauscharm

(SPS6518H 531)

- reception system for setting up multi-subscriber satellite systems in combination with a multi switch
- suitable for multifeed systems
- F connectors are protected by extendible weather-resistant cover
- weather protection due to weather-resistant plastic cover
- fully encapsulated housing

## TECHNICAL DATA

Quality	** Professional
Reception system	QUATTRO (4+ Subscribers)
Connections	4x F jack
Input frequency	10,70 - 11,70 GHz (low) 11,70 - 12,75 GHz (high)
Output frequency	950 - 2,150 MHz
Isolation	> 25 dB
Oscillation frequency	9,75 GHz (low) 10,6 GHz (high)
Amplification (typical)	55 dB
Control function	0 kHz (low) 22 kHz (high)

Polarisation	isolation: > 25 dB
Power supply	vertical: 11,5 - 14,2 V horizontal: 15,8 - 19 V
Power consumption	< 110 mA
Feed diameter	40 mm
Material of product	plastic weather-resistant
Colour	light gray
Dimensions (width)	122 mm
Dimensions (height)	79 mm
Dimensions (depth)	50 mm
Packaging	clamshell SF

Last updated: 27.03.2017