



★★★
ULTIMATE



SUN PROTECT - Digital Single LNB

with gold-plated connectors

When the sun is shining, extremely high temperatures (up to 200° C) can occur on the LNB feedhorn and cause damages. The header cap of this SCHWAIGER® Single LNB resists temperatures of over 220° C for up to 10 minutes! This Single LNB, which is suitable

for multifeed systems, can be used to establish a digital-enabled satellite system for one subscriber. The gold-plated F connectors are protected by an extendible weather-resistant cover.



ARTICLE INFORMATION

Article Nr
EAN

SPS6810R 511
4004005717327



4 004005 717327

Last updated: 21.02.2017



**LOW
NOISE**
Rauscharm

(SPS6810R 511)

- reception system for setting up a satellite system for 1 subscriber
- suitable for multifeed systems
- extremely heat-resistant feedhorn cap (permanently: 150° C, 20 min. between 150° C - 200° C, 10 min. over 220° C)
- F connectors are protected by extendible weather-resistant cover
- weather protection due to weather-resistant plastic cover
- fully encapsulated housing
- best conductivity through gold-plated contacts
- suitable for reception of ASTRA (19.2° East) and EUTELSAT (13° East)

TECHNICAL DATA

Quality	*** Ultimate
Connections	1 x F jack
Plugs	metal gold-plated
Input frequency	10,7 - 11,7 GHz (low) 11,7 - 12,75 GHz (high)
Output frequency	950 - 2,150 MHz
Oscillation frequency	9,75 GHz (low) 10.6 GHz (high)
Amplification (typical)	> 55 dB
Control function	0 kHz (low) 22 kHz (high)

Polarisation	isolation: > 20 dB
Power supply	vertical: 11,5 - 14,5 V horizontal: 15,5 - 19 V
Power consumption	typ. < 130 mA
Feed diameter	40 mm
Material of product	plastic weather-resistant
Colour	Ziegelrot
Dimensions (width)	100 mm
Dimensions (height)	76 mm
Dimensions (depth)	33 mm
Packaging	carton

Last updated: 21.02.2017